



NOTES


- OVERCROSSINGS OF SRP IRRIGATION PIPE ARE REVIEWED ON A CASE-BY-CASE BASIS. EXCEPT FOR THOSE CASES SPECIFICALLY IDENTIFIED BELOW, OVERCROSSINGS ARE TYPICALLY NOT ALLOWED.
- MAINTAIN MINIMUM 3' CLEARANCE BETWEEN SRP IRRIGATION PIPE AND OVERCROSSING SINGLE-SERVICE (RESIDENTIAL) UTILITY LINES OF 1' DIAMETER OR LESS, STREET LIGHT ELECTRIC LINES, OR TRAFFIC SIGNAL ELECTRIC LINES.
- MAINTAIN MINIMUM 12' CLEARANCE BETWEEN SRP IRRIGATION PIPE AND CLOSEST POINT OF OVERCROSSING SCUPPER. SCUPPER SHALL CONFORM TO MAG STANDARD DETAIL 203 OR 206.
- UTILITIES PARALLEL TO SRP IRRIGATION PIPE ARE REVIEWED ON A CASE-BY-CASE BASIS. LOCATE PARALLEL UTILITY OUTSIDE OF AREA SRP EXCAVATES WHEN MAINTAINING IRRIGATION PIPE. TYPICAL EXCAVATION INCLUDES AREA ABOVE AND TO EACH SIDE OF SRP IRRIGATION PIPE. SIDE EXCAVATION INCLUDES AREA ABOVE A LINE EXTENDING UPWARD AND OUTWARD AT A ONE-TO-ONE SLOPE FROM A POINT LEVEL WITH THE BOTTOM OF AND TWO FEET BEYOND THE SIDE OF THE OUTSIDE BELL DIAMETER OF THE SRP IRRIGATION PIPE.
- OTHER UTILITIES NOT PERMITTED IN THESE AREAS.
- CLEARANCE IS MEASURED FROM OUTSIDE BELL DIAMETER OF SRP IRRIGATION PIPE. OUTSIDE BELL DIAMETER IS SIGNIFICANTLY LARGER THAN NOMINAL PIPE SIZE (INSIDE DIAMETER) NOTED ON PLAN/PROFILE DRAWINGS. SEE TABLE FOR NOMINAL PIPE SIZES AND OUTSIDE BELL DIAMETERS.
- SPECIFIED CLEARANCES ARE FOR USE WITH RUBBER GASKETED REINFORCED CONCRETE PIPE (RGRCP) UP TO AND INCLUDING 72" NOMINAL PIPE SIZE. GREATER CLEARANCE OR REPLACEMENT IS REQUIRED FOR LARGER DIAMETER RGRCP, CAST-IN-PLACE PIPE (CIPP) AND NON-REINFORCED CONCRETE PIPE.
- ASSURE CONTINUOUS SUPPORT AND PROTECTION OF SRP IRRIGATION PIPE. DAMAGE TO SRP IRRIGATION PIPE/SYSTEM WILL BE REPAIRED BY SRP. ALL DIRECT AND INDIRECT COSTS SHALL BE BORNE BY OTHER UTILITY/LICENSEE.
- TRENCH BACKFILL COMPACTION SHALL BE MARICOPA ASSOCIATION OF GOVERNMENTS (MAG) TYPE I OR TYPE III, EXCEPT THAT 95% COMPACTION SHALL BE REQUIRED FROM ONE FOOT ABOVE TOP OF PIPE TO BOTTOM OF TRENCH. WATER CONSOLIDATION IS NOT PERMITTED.
- COMPLY WITH MAG UNIFORM STANDARD SPECIFICATIONS AND STANDARD DETAILS UNLESS OTHERWISE NOTED IN PROJECT SPECIFIC SRP DOCUMENTS. MOST STRINGENT REQUIREMENTS SHALL APPLY UNLESS SPECIFICALLY NOTED OTHERWISE IN SRP DOCUMENTS.
- COMPLY WITH ALL APPLICABLE STATUTES, ORDINANCES AND REGULATIONS INCLUDING BLUE STAKE LAW (A.R.S. SEC. 40-360-21 ET SEQ.).
- THESE GUIDELINES ARE PROVIDED AS A GENERAL AID TO PLANNING. ACTUAL SRP REQUIREMENTS MAY VARY BASED ON SITE-SPECIFIC CONDITIONS, OPERATIONAL CONSIDERATIONS, ETC.
- AN SRP LICENSE IS REQUIRED FOR UTILITIES CROSSING/PARALLEL TO SRP IRRIGATION PIPE IN SRP RIGHT-OF-WAY. SRP REQUIRES ENGINEER DESIGNED UTILITY CROSSING/LOCATION AND EXCAVATION PLAN.
- REQUESTS FOR SRP LICENSES ARE HANDLED ON A CASE-BY-CASE BASIS. CONTACT SRP AT 602-236-2962 REGARDING LICENSES FOR SITES LOCATED NORTH OF THE SALT RIVER AND AT 602-236-5799 REGARDING LICENSES FOR SITES SOUTH OF THE SALT RIVER.
- NOTIFY SRP INSPECTOR A MINIMUM OF 72 HOURS BEFORE STARTING CONSTRUCTION IN OR AROUND SRP IRRIGATION FACILITIES. AN IRRIGATION OUTAGE AGREEMENT MUST BE COMPLETED BY THE CONTRACTOR IF A DRY-UP OF ANY PART OF THE IRRIGATION SYSTEM WILL BE NECESSARY DURING CONSTRUCTION. ISSUANCE OF A LICENSE DOES NOT PROVIDE FOR A CONSTRUCTION DRY-UP.



PIPELINE - UTILITY CROSSING



PIPELINE - PARALLEL UTILITY



NOMINAL PIPE SIZE (I. D.)	OUTSIDE PIPE DIAMETER AT BELL (O. D.)
24"	37"
30"	45"
36"	53"
42"	60"
48"	68"
54"	75"
60"	82"
66"	89"
72"	91"

OUTSIDE DIAMETER SRP IRRIGATION PIPE

REFERENCES

SALT RIVER PROJECT RIGHT-OF-WAY GUIDELINES—WES-ROWGUIDE

REVISIONS

REV NO.	DFTR	DSGN	ENGR CHK	ISSUE AUTH	DATE
ADDED NOTE 3 AND RENUMBERED SUBSEQUENT NOTES.					
3	JWS	CWT	CWT	REL	10/18/05
	JWS	CWT	CWT	REL	
INITIAL ISSUE.					
0	MOD	CWT	CWT	REL	04/06/98
	MOD	CWT	CWT	REL	

SALT RIVER PROJECT
WATER ENGINEERING STANDARD

UTILITIES CROSSING OR PARALLEL TO SRP IRRIGATION PIPE

SCALE: NONE 02604001.WES

DWG SIZE

17X22

WES-02604-001